

# MATERIAL SAFETY DATA SHEET

Sunoco Gearol B2

Date issued: 27/10/2003

Date revised: 28/08/2008



Directive 91/155/EEC

## 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY

### 1.1 Identification of the substance or preparation:

**Product name:** Sunoco Gearol B2

### 1.2 Use of the substance or preparation:

Open gear grease (aerosol)

### 1.3 Company/undertaking identification:

Petronas Lubricants Belgium NV  
Ingberthoeveweg 4  
2630 Aartselaar  
Belgium  
Phone: +32 - (0)3 - 458 12 30  
Fax: +32 - (0)3 - 458 14 78  
e-mail: tcs@be.petronas.com

### 1.4 Emergency telephone:

Poisons Centre  
Rue Bruynstraat  
B -1120 Brussel / Bruxelles  
Belgium  
Phone: +32 - (0)70 - 245 245

## 2. HAZARDS IDENTIFICATION

Extremely flammable.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Components	EC nr	CAS no	Weight %	Symbol	R - phrases
Naphta, hydrogen treated light	265-151-9	64742-49-0	20 ... 25	Xn;F;N	11-38-67-65-51/53
Propane /Butane	200-827-9 203-448-7	74-98-6 106-97-8	20 ... 25	F+	12
Isobutane	200-857-2	75-28-5	10 ... 25	F+	12

# MATERIAL SAFETY DATA SHEET

Sunoco Gearol B2

Date issued: 27/10/2003

Date revised: 28/08/2008



## 4. FIRST AID MEASURES

### **Inhalation:**

In case of inhalation of fumes, terminate the exposure and go in de fresh air immediately.  
Inhalation of fumes, vapours or aërosols can cause slight irritation of the respirations ways.

### **Ingestion:**

If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.  
Do not give water.

### **Skin contact:**

Remove contaminated clothing and wash thoroughly the skin with soap or detergent and water.  
Wash thoroughly the skin with water and soap.

### **Eye contact:**

Flush thoroughly with running water during 15 minutes (including under eyelids).

## 5. FIRE-FIGHTING MEASURES

### **Suitable extinguishing media:**

CO<sub>2</sub> , foam or dry chemicals.

### **Extinguishing media which must not be used for safety reasons:**

Do not use water jet.

### **Special exposure hazards arising from the substance or preparation itself, combustion products, resulting gases:**

Smoke and carbon monoxide may be formed in the event of incomplete combustion.

### **Special protective equipment for fire-fighters:**

Wear an approved autonomous breathing apparatus and protective clothing.

## 6. ACCIDENTAL RELEASE MEASURES

### **Personal precautions:**

Avoid contact with skin and eyes.  
Take off immediately all contaminated clothing.

### **Environmental precautions:**

Prevent this product from entering into contact with surface waters

### **Methods for cleaning up:**

To clean the floor and all objects contaminated by this material, use sand, active clay .

# MATERIAL SAFETY DATA SHEET

Sunoco Gearol B2

Date issued: 27/10/2003

Date revised: 28/08/2008



## 7. HANDLING AND STORAGE

### 7.1 Handling

A sufficient ventilation must guarantee an exposure which do not exceed the acceptable limit.

Keep away from combustible material.

Keep away from food, drink and animal feeding stuffs.

Take precautionary measures against static discharges.

### 7.2 Storage

Keep away from sources of ignition - No smoking.

Store in a closed packing and away from heath sources.

Avoid high temperatures and humidity.

Keep container tightly closed and dry.

### 7.3 Specific use(s)

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1 Exposure limit values

Sufficient ventilation should be provided in order to maintain fumes concentration in the air bellow the occupational exposure limit.

Components with exposure limits
106-97-8 Butane
MAC ( ) : 1430 mg/m <sup>3</sup> , 600 ppm

### 8.2 Exposure controls

#### 8.2.1 Occupational exposure controls

##### 8.2.1.1 Respiratory protection:

Inhalation of vapours or fumes has to be avoided through accurate ventilation and safe working circumstances.

##### 8.2.1.2 Hand protection:

Wear rubber gloves.

##### 8.2.1.3 Eye protection:

Wear safety glasses if eye contact is possible.

##### 8.2.1.4 Skin protection:

Overall, or similar full-body work clothes, gloves and shoes.

#### 8.2.2 Environmental exposure controls

# MATERIAL SAFETY DATA SHEET

Sunoco Gearol B2

Date issued: 27/10/2003

Date revised: 28/08/2008



## 9. PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 General information

Appearance: Aërosol liquid  
Odour: Characteristic

### 9.2 Important health, safety and environmental information

Flash point: <0°C  
Explosive properties: Limits: LEL 1.1 vol%; UEL 10.9 vol%

Oxidizing properties: Not applicable  
Vapour pressure: 3500 hPa (2625 mm Hg) @ 20°C  
Relative density: Density : approx. 0.66 g/cm<sup>3</sup>  
Solubility: - watersolubility: insoluble in water  
Solubility: - fatsolubility (solvent-oil): insoluble in water

### 9.3 Other information

Miscibility: Not resp. little miscible  
Melting point / melting range: Not applicable  
Auto-ignition temperature: Not self inflammable  
Other data: VOC content : 53.8 %

## 10. STABILITY AND REACTIVITY

- 10.1 Conditions to avoid:** Keep away from heat sources, open flames and other sources of ignition.
- 10.2 Materials to avoid:** Avoid contact with strong oxidants.
- 10.3 Hazardous decomposition products:** Incomplete burning can cause formation of dangerous gasses like CO, CO<sub>2</sub>, different KWS, aldehyde and also soot.

## 11. TOXICOLOGICAL INFORMATION

### ACUTE TOXICITY

#### **64742-49-0 Nafta (petroleum), hydrotreated light.**

Oral LD50 >5000 mg/kg (rat)  
Dermal LD50 >2600 mg/kg (rabbit)  
Inhalation LC50/4h >193 mg/l (rat)

#### **106-97-8 Butane**

Inhalation LC50/4h 658 mg/l (rat)

# MATERIAL SAFETY DATA SHEET

Sunoco Gearol B2

Date issued: 27/10/2003

Date revised: 28/08/2008



## 12. ECOLOGICAL INFORMATION

### 12.1 Ecotoxicity:

Aquatic organisms, Algea IC50 (72 h):	Unknown
Aquatic organisms, Daphnia magna EC50 (48h):	Unknown
Aquatic organisms, Fish LC50 (96h):	Unknown
Plants and terrestrial animals:	Unknown
Soil organisms:	Unknown
Impact on sewage treatment plants:	Unknown

### 12.2 Mobility:

Known or predicted distribution to environmental compartments:  
Low range of mobility in the soil. Some components can penetrate the soil and cause pollution of the ground water.

Surface tension:	Not applicable
Absorption/adsorption:	Not applicable

### 12.3 Persistence and degradability:

Not easily biodegradable.

### 12.4 Bioaccumulative potential:

Base oil components are probably not dangerous for water organisms. Some additives may be dangerous for the aquatic environment.

### 12.5 Other adverse effects:

Ozone depletion potential:	Not applicable
Photochemical ozone creation potential:	Not applicable
Global warming potential:	Not applicable

## 13. DISPOSAL CONSIDERATIONS

Waste disposal methods must comply with national and local disposal or discharge laws.

# MATERIAL SAFETY DATA SHEET

Sunoco Gearol B2

Date issued: 27/10/2003

Date revised: 28/08/2008



## 14. TRANSPORT INFORMATION

<b>UN - number:</b>	UN N° : 1950
<b>Proper shipping name:</b>	Aerosol
<b>IMDG</b>	
Class:	9
Other applicable information:	Page 9022 etiquette 9 Packing group II MFAG 602 EMS 2-13
Marine pollutant:	
<b>ADR/RID</b>	
Class:	2.10.b2
Other applicable information:	Etiquette 3
<b>ICAO/IATA</b>	
Class:	2
Other applicable information:	Packing group : II ; Packing instructions 203

## 15. REGULATORY INFORMATION

This Safety Data Sheet has been established in accordance with E. C. Directive nr. 91/155/ECC

Danger symbol:



F+

Risk - sentences:  
12  
Extremely flammable

Safety - sentences:  
2  
46  
61  
2 – 46 – 61  
Keep out of the reach of children.  
If swallowed, seek medical advice immediately and show this container or label.  
Avoid release to the environment. Refer to special instructions/Safety data sheets.

Please refer to any other national regulations that may be applicable for this product.

Other regulatory information:

# MATERIAL SAFETY DATA SHEET

Sunoco Gearol B2

Date issued: 27/10/2003

Date revised: 28/08/2008



## 16. OTHER INFORMATION

### Training advice:

### Recommended restrictions on use:

### Further information (written references and/or technical contact point):

FULL TEXT OF RISK PHRASES APPEARING IN SECTION 2

R 12 : Extremely flammable

R 38 : Irritating to skin

R 51/53 : Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 67 : Vapours may cause drowsiness and dizziness.

R 65 : Harmful : may cause lung damage if swallowed.

### Source of key data used to compile the data sheet:

### Information added, deleted or revised:

These data are based upon our knowledge at this moment. It is however no guarantee for product properties and do not have a contractual agreement.

The buyer assumes all risk in connection with the use and handling of the material.

The seller assumes no responsibility or liability in connection with the information supplied in this sheet or for any damage or injury caused by the material; reasonable safety procedures should be followed.

The seller assumes no responsibility for injury or damage caused by use of the material, even if reasonable safety procedures are followed.

The information contained in this sheet is developed from what is believed to be accurate and reliable sources but the seller makes no warranties, either expressed or implied and assumes no responsibility for the accuracy or completeness of the data contained herein.