

Product information



SUNOCO

2T Snow Superior

Description Top tier, semi-synthetic, low smoke/low ash, highly performant 2 cycle snow scooter motor oils for "pre-mixed" as well as for injection system use.

Application Used in the major part snowmobile models: - ARCTO (Arctic Cat); BOMBARDIER (Ski-Doo) (Grand sport, Cross Country models ZX-X, SC-10, MXZ, Deep snow Summit en Grand Touring en Utility Skandic WT/LT en Alpine models,...); LYNX (GLX, ST en Forest Sox S, Safari, Explorer en Ranger models...); YAMAHA (autolube models)...

Specifications

- CEC TSC-4 / API TC+ / JASO FC / Global ISO-L-EGD
- PIAGGIO HEXAGON
- APRILIA SR 50 DiTech
- ROTAX 253

Properties

- self mixing semi-synthetic, "low ash" lube oil formulation for demanding current air cooled two stroke snowmobile engines
- highly detergent, prevents bearing corrosion, spark plug fouling and exhaust port clogging
- excellent bearing and cylinder lubrication, minimum smoke and odor development
- very low pour point as well as excellent low temperature fluidity for proper and uninterrupted injection system serviceability in extremely cold temperature conditions, full exhaust gas catalyst compatibility

Typical analysis :

Density at 15°C	0.880	Pour point °C	-39
Viscosity at 40°C / cSt	63.5	TBN mg KOH/g	1.8
Viscosity at 100°C / cSt	10.1	TAN mg KOH/g	0.5
Viscosity at -10°C / cP	1300	Sulphated ash / %	0.1
Viscosity index	140	Colour	3.0
Flash point °C	101		

All technical data is provided for reference only.

6 - 2009