

Product information



SUNOCO 2T Superior

Description Upper tier, semi-synthetic, low smoke type, two stroke motor oil for "premixed" as well as for injection system use.

Application For virtually all two stroke engines: premixed (standard ratio 1:50 or according OEM prescriptions) or in separate lubricant reservoir.

- Motorcycles, mopeds and go-carts.
- Electricity generators and portable power units.
- ULM type planes (with ROTAX engine).
- Lawnmowers and powered garden equipment.
- Chainsaws, including STIHL and HUSQVARNA models.
- snowmobiles / snow scooters.

Specifications

- CEC TSC – 4 / API TC
- PIAGGIO SI
- TISI 2 stroke
- exceeding the SWEDISH Machinery Testing Institute/Umea and the "SNOSKOOTER" magazine "semi-official" and popular ROTAX 253 lube oil standard.
- Global ISO-LEGD
- JASO (M35-93) FC

Properties

- Self mixing.
- Highly detergent, prevents bearing corrosion, spark plug fouling and exhaust pollution of the sparking plug.
- Excellent cylinder and bearing lubrication.
- Mixing ratio 1 : 50 or according to manufacturers' instructions.
- Minimum smoke and odour formation.
- Low ash content.
- Engines keep extremely clean internally.

Typical analysis :

Density at 15°C	0.864	Flash point °C	100
Viscosity at 40°C / cSt	66.5	Pour point °C	-36
Viscosity at 100°C / cSt	10.3	TAN mg KOH/g	0.5
Viscosity at -10°C / cP	1400	TBN mg KOH/g	1.8
Viscosity index	143	Colour	L3.0

All technical data is provided for reference only.

6 - 2009