

Product information



SUNOCO 2T ECO

Description Flagship two cycle lube for top engine performance. Quickly biodegradable and fully synthetic. For both air and water cooled two stroke engines.

Application Used as high performance oil for following purposes:

- outboard engines and water scooters.
- motorcycles, mopeds and go-carts.
- mobile/portable power units
- 2 stroke lawnmowers and other powered garden equipment.
- chainsaws, including STIHL and HUSQVARNA models.
- snowmobile/snow scooters and ROTAX powered ULM planes.

Specifications

- NMMA TC-W3
- CEC L-33-T-82 biodegradability above 66%, typically 82%

Properties

- environmentally friendly through high biodegradability.
- easy mixing, even at sub zero temperatures, forms immediately and permanently an homogeneous mixture for full power availability.
- Highly detergent, prevents bearing corrosion, spark plug fouling and exhaust port clogging.
- Excellent bearing and cylinder lubrication.
- Minimum smoke and odour development.
- Ashless formulation.
- Low pour point as well as exceptional low temperature fluidity.
- Exhaust gas catalyst compatibility.

Typical analysis :

Density at 15°C	0.914	Pour point °C	<-40
Viscosity at 40°C / cSt	24.6	TBN mg KOH/g	4
Viscosity at 100°C / cSt	5.3	Sulphated ash	nihil
Viscosity index	156	Colour	5.5
Flash point °C	103		

All technical data is provided for reference only.

10 - 2009