

Product information



SUNOCO 4T GP Power

Description High quality mineral engine oil, reinforced with the latest additive technologies, for 4 stroke motorcycles operating under both varying conditions as well as under continuously high speeds.

Application Specifically recommended for 4 stroke motorcycles of following makes : BMW, HARLEY DAVIDSON, MAGNI, MOTO GUZZI, HUSQVARNA, YAMAHA,... Particularly suitable for many touring/tourist type and /or chopper models. This oil is also suitable for the lubrication of the engine integrated clutch with common oil bath.

Specifications

- SAE 15W50
- API SH
- ACEA A2
- JASO MA

Properties

- Excellent protection against wear and corrosion through the perfectly resistant oil film resulting in high serviceability and extended lifetime.
- The very efficient dispersant additives prevent formation of deposits on engine parts.
- Perfect lubrication at all temperature conditions.
- Fully compatible with/ not harmful to exhaust gas catalysers.

Typical analysis :

Density at 15°C	0.886
Viscosity at 40°C / cSt	130
Viscosity at 100°C / cSt	19.0
Viscosity at -15°C / cP	3300
Flash point °C	220
Pour point °C	-30
TBN mg KOH/g	10
Colour	3.0

All technical data is provided for reference only.

6 - 2009