

## Product information



# SUNOCO

## Antifreeze 50/50 Coolant

**Description** Antifreeze 50/50 Coolant is a product based on mono-ethylene glycol, demineralised water and additives that takes care of an efficient and good cooling of gasoline, diesel and LPG engines with open or closed cooling systems.

**Properties**

- Nitrite, amine and phosphate free cooling medium that protects the ferro- and nonferrous (aluminium) metals in the cooling system against corrosion, freezing and overheating.
- Mono-ethylene glycol and a number of carefully selected additives to protect the metals in the cooling system against corrosion and rust.
- Does not attack the flexibles or gaskets.( rubber and elastomers )
- Has excellent anti-foam properties.

**Meets**

- BS 6580
- AFNOR 15601
- ASTM D 3306 ( ASTM D 4656 )
- CUNA NC 956-16
- Ö-norm
- SAE J 1034

### Typical analysis :

Density at 15°C	1.070
Colour	blue
pH	7.6-8.0
Pour point °C max.	-36°C
Boiling point °C	107
Corrosion test ( ASTM D 1384) / mg/cm <sup>3</sup> :	
- copper	0.1 max
- solder	0.3 max
- brass	0.1 max
- steel	0.1 max
- iron	0.1 max
- aluminium	0.2 max

All technical data is provided for reference only.

11 - 2010