

Product information



SUNOCO

Heavy Duty Synto HPD 5W30

Description Upper tier, fully synthetic, low viscosity and fuel economy heavy duty diesel engine oil for trucks and busses.

Application For the major part of modern trucks and busses with or without turbo charger.

Specifications

- ACEA E7 / E4
- API CF
- Cummins CES 20071 / 20072 / 20076 / 20077
- DAF HP1 / HP2
- Iveco 18-1804
- Mack EO-M Plus
- MAN M3277
- MB 228.5
- MTU Type 3
- Renault RVI-RXD
- Volvo VDS-3

Properties

- Fully synthetic, highly resistant HD diesel engine oil formulation.
- For OEM maximum allowable drain intervals.
- Fuel economy since both SAE 5W and SAE 30 viscosity.
- Highest possible soot dispersant and detergent capability.
- Super low "bore-polishing" effect.
- All season/different climate suitability in modern engines equipments.

Typical analysis :

Density at 15°C	0.860
Viscosity at 40°C / cSt	67
Viscosity at 100°C / cSt	11.4
Viscosity at -30°C / cP	<6600
Viscosity index	165
Flash point °C	220
Pour point °C	-36
TBN mg KOH/g	16

All technical data is provided for reference only.

12 - 2009