

Product information



SUNOCO

Heavy Duty Super HPD 15W40

Description Highly powered oil for all heavy naturally aspirated and turbo diesel engines, with or without intercooler, with direct or indirect fuel injection.

Application SUPER HPD is the right diesel motor oil for the most severe working circumstances, a real tough "Super High Performance" diesel oil for working under high temperature loads and extended oil drain intervals. Diesel engine oils for busses, machines, trucks as well as in (small) direct injected engines and wherever the beneath oil specifications apply:

Specifications

- API CH-4 / CG-4 / CF / CE / SJ
- ACEA B4 / B3 / E3
- MB 228.3
- VW 505.00
- MTU type 2
- RVI RD
- KHD SHPD oil TRO 199-228.3
- Perkins engines
- VOLVO VDS-2
- MAN M3275
- Mack EO-M
- DAF SHPD oil
- Cummins 20071 / 72

Properties

- Very strong dispersant and detergent SHPD oil.
- Can be used during every season.
- Excellent protection against "bore polishing".
- Extended oil drain intervals.

Typical analysis :

Density at 15°C	0.887
Viscosity at 40°C / cSt	115
Viscosity at 100°C / cSt	15.0
Viscosity at -20°C / cP	<7000
Viscosity index	136
Flash point °C	220
Pour point °C	-33
TBN mg KOH/g	10
Colour	4.5

All technical data is provided for reference only.

6 - 2009