

Product information



SUNOCO

Synturo Diamond 0W40

Description Flagship, fully synthetic lubricating engine oil, particularly developed for the most demanding working circumstances. Especially suitable for use in cold weather areas as well as resistant to high environmental temperature operations.

Application Recommended for virtually all types of gasoline, LPG and diesel latest state of the art (direct injection engines) engines in passenger cars and vans, with or without turbo charging and/or modern multi-valve and variable valve lifter and timing technology. To be applied wherever the beneath engine oil specifications are required.

Specifications

- API SJ / CF
- ACEA A3 / B4
- BMW LongLife 98
- MB 229.3
- Porsche
- VW 502.00 / 503.01 / 505.00

Properties

- Extremely good fluidity at low temperatures.
- Less friction gives fuel-economy & better performance.
- Engines keep internally extremely clean.
- Exhaust gas catalyst compatibility.
- Decrease of combustion exhaust gas emissions.
- Complete engine protection.

Typical analysis :

Density at 15°C	0.861	Pour point °C	< -50
Viscosity at 40°C / cSt	73	TBN mg KOH/g	10.6
Viscosity at 100°C / cSt	13.2	Sulphated ash / %	1.2
Viscosity at -35°C / cP	5700	Noack volatility / %	8.5
Viscosity index	187	HTHS viscosity / cP	3.6
Flash point °C	236	Colour	3.0

All technical data is provided for reference only.

9 - 2009