

Product information



SUNOCO Synturo Dynamic 5W30

Description Unique, carefully fine-tuned, energy conserving, "low viscosity" type engine oil for gasoline, diesel and LPG fuelled cars and light duty vans for whole year use.

Application

- particularly for FORD gasoline engines and diesel engines.
- perfectly applicable and recommended for engines requiring ACEA A5/B5 engine oil.

Specifications

- API SL/CF
- ACEA A5 / B5
- Ford WSS-M2C913-C
- Renault RN0700

Properties

- Lower fuel cost expenses and better exhaust emission control.
- Prevents formation of "black sludge" in gasoline engines.
- Guaranteed easy cold cranking at start-up, even at -30° C.
- The synthetic components give an extreme high thermal stability.
- Unequalled engine protection against wear (lowering maintenance costs).
- Offers instant and excellent lubrication at both high and low operating temperatures over the complete speed range and keeps oil consumption very low at the same time.

Typical analysis :

Density at 15°C	0.851	Flash point °C	224
Viscosity at 40°C / cSt	51	Pour point °C	-42
Viscosity at 100°C / cSt	9.5	Sulphated ash % wt.	1.2.
Viscosity at -30°C / cP	5000	Phosphor %	0.096
Viscosity index	174	Zinc %	0.105
TBN mg KOH/g	9,9		

All technical data is provided for reference only.

4- 2011