

Product information



SUNOCO

Synturo Gold 5W40

Description Fully synthetic lubricating turbo engine oil for passenger cars and vans operating in the most demanding working circumstances and during all seasons, including those related to cold temperature regions.

Application SYNTURO GOLD is recommended for all types of gasoline, LPG and diesel engines, with or without turbo charging in latest generation passenger cars and vans (also with multi valve models), particularly suitable in climatologically cold conditions. To be applied wherever the beneath engine oil specifications are required.

Specifications

- API SL / SJ / CF
- ACEA A3 / B4
- BMW LongLife 98
- MB 229.3
- Porsche
- PSA B71 2296
- VW 502.00 / 505.00

Properties

- Excellent high temperature high shear properties.
- Very low volatility avoiding oil consumption.
- Maximum protection against wear, oxidation, varnish and rust-formation.
- Engines keep internally extremely clean.
- Exhaust gas catalyst compatibility.
- Fuel economy through relatively low lubricating oil viscosity in case of frequent short trip driving.

Typical analysis :

Density at 15°C	0.853	Flash point °C	235
Viscosity at 40°C / cSt	87	Pour point °C	-36
Viscosity at 100°C / cSt	14.3	TBN mg KOH/g	9.1
Viscosity at -30°C / cP	6500	Noack volatility / %	11
Viscosity index	171	HTHS viscosity / cP	3.8

All technical data is provided for reference only.

11 - 2011