

Product information



SUNOCO

Synturo Platinum 5W30

Description Fully synthetic lubricating turbo engine oil for the most demanding working circumstances and during all seasons. Particularly suitable for use in cold temperature regions.

Application SYNTURO PLATINUM is recommended for almost all types of gasoline, LPG and diesel engines, with or without turbo charging in latest generation passenger cars (also with multi valve engines), extremely suitable in cold climatologically conditions. Applied wherever the beneath engine oil specifications with SAE 5W30 viscosity are required.

Specifications

- API SL / SJ / CF
- ACEA A3 / B4
- MB 229.3
- VW 502.00 / 505.00

Properties

- Extremely good fluidity at low temperatures even at -30° C.
- Excellent high temperature high shear properties.
- Very low volatility avoiding oil consumption.
- Maximum protection against wear, oxidation, varnish and rust-formation.
- Engines keep internally extremely clean.
- Exhaust gas catalyst compatible.
- Fuel economy by low lubricating oil viscosity especially interesting in case of frequent short trip driving.

Typical analysis :

Density at 15°C	0.85	Pour point °C	-39
Viscosity at 40°C / cSt	72	TBN mg KOH/g	10.2
Viscosity at 100°C / cSt	11.9	Noack volatility %	11
Viscosity at -30°C / cP	6500	HTHS viscosity / cP	3
Viscosity index	162	Colour	L3.5
Flash point °C	225		

All technical data is provided for reference only.

9 - 2009