

Product information



SUNOCO Synturo Xenon 5W30

Description Fully synthetic lubricating engine oil, especially developed the long time protection of the emission system of the modern car and to keep the efficiency of the emission reduction system.

Application Recommended for the modern type of gasoline, LPG and diesel engine, with or without turbo charging, in latest generation passenger cars equipped with diesel particulate filter (DPF) and / or performant catalytic convertor (SCR).

Specifications

- API SM / CF
- ACEA C3 & A3 / B4
- BMW LongLife 04
- MB-Approval 229.51
- GM Dexos 2

Properties

- Low ash level, phosphor and sulphur, extending life time of the car's emission control system while keeping up its efficiency.
- Good fluidity at low temperatures enhances cold start performance.
- Less friction gives fuel-economy & better performance, with lower CO2 emission.
- Engines keep internally extremely clean, extending the engine life time.
- High quality for stable, optimum performance and extended oil drain intervals.

Typical analysis :

Density at 15°C	0.855
Viscosity at 40°C / cSt	72
Viscosity at 100°C / cSt	12
Viscosity at -30°C / cP	6500
Viscosity index	165
Flash point °C	226
TBN mg KOH/g	7,2
Pour point °C	-39
HTHS viscosity	3,7
Colour	3.0

All technical data is provided for reference only.

1 - 2011