

Product information



SUNOCO

Kratos Hitrac 10W40

Description Semi-synthetic multifunctional oil for industrial construction side machinery, agricultural and horticultural equipment as well as for compressors.

Application For use in "bulldozers", industrial and agricultural tractors, construction machines and compressors. Works as motor oil, hydraulic oil, gear oil, wet brake fluid as well as in a large number of transmissions and compressors.

Specifications

<u>Motoren</u> API CG-4/CF-4/CF/CE/CD ACEA E3 MIL-L-2104D/46152C MB227.1/MB228.1 MAN 271	<u>S.T.O.U.</u> MF M1145/M1144/M1139
--	--

<u>Transmissies</u> API GL-4/5 Allison C4 ZF TE-ML-06B/06F/07B CAT TO-2	<u>Compressoren</u> Atlas Copco Holman Compair Hydrovane	<u>Hydrauliek</u> Vickers Denison HF-O
--	--	---

Properties

- Guarantees a long lifetime of the engines thanks to the clean working, the stability of the oil film, the resistance against "shear" and the good fluidity at low temperatures.
- Reliable operation of hydraulic systems thanks to the good filterability, the excellent anti-wear properties, the wide temperature application range and compatibility with gaskets.
- EP properties allow high torque transmissions.
- Silent and regular working of the wet brakes.

Typical analysis :

Density at 15°C	0.875	Viscosity index	151
Viscosity at 40°C / cSt	91.2	Flash point °C	210
Viscosity at 100°C / cSt	13.6	Pour point °C	-36
Viscosity at -25°C / cP	<7000	TBN mg KOH/g	10.5

All technical data is provided for reference only.

11 - 2011