

# Product information



## SUNOCO Kratos Agrotrac range

- Description** Oil type "S.T.O.U." to be used in engines, wet brakes, transmissions and hydraulic system of the agricultural tractor.
- Application** Recommended for a wide range of tractor equipment ( gasoline or diesel ) with or without turbo. The good fluidity at low temperatures and the high relative viscosity at high temperatures give a good application for gears both in tropical climate and in freezing conditions.
- Specifications**
- API CD / SF / GL-4
  - CCMC G2 / D2
  - Ford M2C159-B/C
  - MIL-L-2104C & D / MIL-L-46152C / MIL-L-2105
  - Massey Fergusson M1139/M1144
  - ZF TE-ML 06
  - Vickers Hydraulic Pump System
- Properties**
- Universal oil for tractors (industrial and agricultural) and all workshop materials.
  - Utilisation in tropical climate and by freezing temperatures.
  - Reduces noise due to working of immersed brakes.
  - Less failures possible because one product is used.
  - Anti-wear characteristics.

### Typical analysis :

SAE	10W30	15W30	15W40	20W40
density at 15°C	0.882	0.887	0.886	0.892
viscosity at 40°C / cSt	64.7	74.3	99.0	122.4
viscosity at 100°C / cSt	10.3	10.4	13.6	13.7
viscosity at -15°C / cP	-	-	-	<9500
viscosity at -20°C / cP	-	<7000	<7000	-
viscosity at -25°C / cP	<7000	-	-	-
viscosity index	145	124	150	109
flash point °C	195	210	200	225
pour point °C	-36	-30	-30	-37
TBN mg KOH/g	10.5	10.5	10.5	10.5
colour	4.5	L5.0	5.0	L5.0

All technical data is provided for reference only.

07 - 2010