

Product information



SUNOCO

Kratos Bultrac range

Description Multifunctional oil for industrial construction side machinery, agricultural and horticultural equipment as well as for compressors.

Application For use in "bulldozers", industrial and agricultural tractors, construction machines and compressors. Works as motor oil, hydraulic oil, gear oil, wet brake fluid as well as in a large number of transmissions and compressors.

Specifications

<u>Motoren</u> API CG-4/CF-4/CF/CE/CD ACEA E3 MIL-L-2104D/46152C MB227.1 MAN 271	<u>S.T.O.U.</u> MF M1145/M1144/M1139
--	--

<u>Transmissies</u> API GL-4/5 Allison C4 ZF TE-ML-06B/06F/07B CAT TO-2	<u>Compressoren</u> Atlas Copco Holman Compair Hydrovane	<u>Hydrauliek</u> Vickers Denison HF-O
--	--	---

Properties

- Guarantees a long lifetime of the engines thanks to the clean working, the stability of the oil film, the resistance against "shear" and the good fluidity at low temperatures.
- Reliable operation of hydraulic systems thanks to the good filterability, the excellent anti-wear properties, the wide temperature application range and compatibility with gaskets.
- EP properties allow high torque transmissions.
- Silent and regular working of the wet brakes.

Typical analysis :

SAE	10W40	15W30	15W40
density at 15°C	0.880	0.887	0.886
viscosity at 40°C / cSt	85.8	74.3	99.0
viscosity at 100°C / cSt	13.5	10.4	13.6
viscosity at -20°C / cP	-	<7000	<7000
viscosity at -25°C / cP	<7000	-	-
viscosity index	160	124	150
flash point °C	220	210	200
pour point °C	-27	-27	-27
TBN mg KOH/g	10.5	10.5	10.5

All technical data is provided for reference only.

11 - 2011