

## Product information



# SUNOCO

## Kratos Bultrac range

**Description** Multifunctional oil for industrial construction side machinery, agricultural and horticultural equipment as well as for compressors.

**Application** For use in "bulldozers", industrial and agricultural tractors, construction machines and compressors. Works as motor oil, hydraulic oil, gear oil, wet brake fluid as well as in a large number of transmissions and compressors.

**Specifications**

<b><u>Motoren</u></b> API CG-4/CF-4/CF/CE/CD ACEA E3 MIL-L-2104D/46152C MB227.1 MAN 271	<b><u>S.T.O.U.</u></b> MF M1145/M1144/M1139 Ford M2C159-B/C FNH 82009201/2/3 NH 030 C & NH 024 C
--	--

**Transmissies**

API GL-4/5  
Allison C4  
ZF TE-ML-06/07  
CAT TO-2

**Compressoren**

Atlas Copco  
Holman Compair  
Hydrovane

**Hydrauliek**

Vickers  
Denison HF-O

**Properties**

- Guarantees a long lifetime of the engines thanks to the clean working, the stability of the oil film, the resistance against "shear" and the good fluidity at low temperatures.
- Reliable operation of hydraulic systems thanks to the good filterability, the excellent anti-wear properties, the wide temperature application range and compatibility with gaskets.
- EP properties allow high torque transmissions.
- Silent and regular working of the wet brakes.

### Typical analysis :

SAE	10W40	15W30	15W40
density at 15°C	0.880	0.887	0.886
viscosity at 40°C / cSt	85.8	74.3	99.0
viscosity at 100°C / cSt	13.5	10.4	13.6
viscosity at -20°C / cP	-	<7000	<7000
viscosity at -25°C / cP	<7000	-	-
viscosity index	160	124	150
flash point °C	220	210	200
pour point °C	-33	-30	-30
TBN mg KOH/g	10.5	10.5	10.5

All technical data is provided for reference only.

07 - 2010