

Product information



SUNOCO Standard Super range

Description Universal oil for all turbo charged and naturally aspirated engines in passenger cars, trucks, busses and machinery, all working under severe circumstances.

Application As described by the below mentioned specifications. Can also be used as transmission oil of certain off-the-road machinery and busses.

Specifications

- SAE 10W40 / 15W40 / 20W50
- API SF / CE
- MIL-L-2104D / MIL-L-46152C
- CAT TO-2
- MAN 271
- MB 227.5
- VW 501.01/505.00
- Volvo VDS

Properties

- Extremely detergent universal oil.
- Can be poured out into practically any crankcase you have.
- Extended drain properties.

Typical analysis :

SAE	10W40	15W40	20W50
Density at 15°C	0.880	0.885	0.892
Viscosity at 40°C / cSt	88	100	153
Viscosity at 100°C / cSt	13.5	13.6	17.5
Viscosity at -25°C / cP	<7000	-	-
Viscosity at -20°C / cP	-	<7000	-
Viscosity at -15°C / cP	-	-	8000
Viscosity index	154	139	125
Flash point °C	220	220	230
Pour point °C	-36	-30	-27
TBN mg KOH/g	8.5	8.5	8.5
Colour	L4.5	4.5	5.5

All technical data is provided for reference only.

4- 2011