

Product information



SUNOCO Standard Universal Multi range

- Description** Universal oil for a mixed fleet of cars.
- Application** Standard Universal Multi is used as motor oil for naturally aspirated and turbo diesel engines. Also for some transmission lubrication of ground moving equipments.
- Specifications**
- SAE 10W30 / 15W50 / 20W40 / 20W50
 - API SE / CD
 - MIL-L-46152C / MIL-L-2104D
 - CAT TO-2
 - GM 6041M / 6136M
 - Mack EO-H
 - MB 227.1 / 226.1
 - VW 505.00
- Properties**
- Universal motor oil.
 - Long drain properties.
 - Keeps the engine clean.

Typical analysis :

SAE	10W30	15W50	20W40	20W50
Density at 15°C	0.878	0.883	0.893	0.893
Viscosity at 40°C / cSt	70	128	119	153
Viscosity at 100°C / cSt	10.5	17.0	13.6	17.5
Viscosity at -25°C / cP	6300	-	-	-
Viscosity at -20°C / cP	-	6500	-	-
Viscosity at -15°C / cP	-	-	7600	7600
Viscosity index	137	145	111	125
Flash point °C	210	230	240	240
Pour point °C	-30	-27	-27	-27
TBN mg KOH/g	5,3	5,3	5,3	5,3
Colour	L4.5	L4.5	L5.0	5.5

All technical data is provided for reference only.

11 - 2011