

# Product information



## SUNOCO Sunamatic ATF DEX III

**Description** ATF designed to protect most passenger car, van and light truck automatic transmissions.

**Application** Wherever DEXRON III, DEXRON II-E, DEXRON II, DEXRON or Type A fluids are recommended. Wherever MERCON, M2C138-CJ or M2C166-H fluids are recommended. In all automatic transmissions built by GM. Wherever Allison C-4 fluids are required.  
May be used in some hydraulic and compressor systems where excellent low temperature flowability is required.

**Specifications**

- Dexron III G-34014	MB 236.9
- Ford Mercon M940209	VOITH
- Allison C-4 20952194	

**Advantages**

Additional savings that result from using just one fluid for most automatic transmission applications.

Oxidation resistance: product is formulated with excellent base stocks and special additives that minimize deterioration of the fluid through use.

Improved low temperature fluidity: excellent protection against wear during cold operating conditions and helps eliminate cold start stalling.

Transmission cleanliness: the additives prevent formation of deposits which affect the performance of delicate control valves.

Viscosity index: excellent performance over a wide range of temperatures is possible through the use of high VI base oils along with a shear stable VI improver.

### Typical analysis :

Density at 15°C	0.865
Viscosity at 40°C / cSt	33
Viscosity at 100°C / cSt	7.5
Viscosity at -40°C / cP	15500
Viscosity index	197
Flash point °C	190
Pour point °C	-48
Colour	red

All technical data is provided for reference only.

6 - 2009