Product information

SUNOCO
Sunamatic ATF DEX VI

Description Sunamatic ATF DEX VI is an exceptional automatic transmissiono fluid, specially developed for use in the latest vehicles equiped with an automatic transmission. In comparison to the Dexron® III fluid, Sunamatic ATF DEX VI has twice the service life and offers enhanced performance for both new and older automatic transmissions.

Application For all modern GM Hydramatic automatic transmissions and wherever Dexron® III-H, Dexron® III and Dexron® II-E is prescribed.

Specifications
- Dexron® VI
- Meets GM N10060

Advantages
- Extended transmission life. Clutch plates and bands last longer.
- Extended drain intervals.
- Outstanding resistance against sludge and deposit.
- Improved oxidation and thermal stability.
- Superior anti-wear properties.
- Outstanding low temperature fluidity.
- Optimized frictional properties.
- Improved Fuel Economy in comparison to ATF Dexron® III.

Typical analysis :

Density at 15°C	0.846
Viscosity at 40°C / cSt	29.8
Viscosity at 100°C / cSt	6.0
Viscosity at -40°C / cP	12030
Viscosity index	151
Flash point °C	206
Pour point °C	-54
Sulphated ash % wt.	0.02
Colour	red

All technical data is provided for reference only. 6 - 2009

Petronas Lubricants Belgium NV
Ingberthoeveweg 4
B-2630 AARTSELAAR
Tel.: +32(0)3 458 12 30
E-mail: tcs@be.petronas.com