

Product information



SUNOCO

Sunamatic ATF S168

Description Fully synthetic automatic transmission fluid.

Application This transmission fluid can be applied in all automatic transmissions for which Dexron II, III, Mercon, Mercon V, LV or SP is being prescribed.

Specifications

- Dexron III-H
- Mercon V, LV, SP
- BMW 7045 E, LA2634, LT71141
- Honda Z1
- Hyundai SP-II/SP-III
- Kia SP-II/SP-III
- MB 236.1/2/5/6/7/9/10
- Mitsubishi SP-II/SP-III
- Nissan Matic D/J/K
- Toyota T/T-III/T-IV/WS
- VAG G-052-025-A2/G-052-162-A1
- Volvo 97340

Properties

- Prevents corrosion and the formation of sludge.
- Compatible with all possible sealing materials used in automatic transmissions.
- Gives a quick and good lubrication at all temperatures.
- The excellent anti wear properties, make the lifetime of the transmission longer and reduce wear of bearings, bushings and cog wheels.
- Thanks to the use of friction stable additives, a smooth shifting is guaranteed.

Typical analysis :

Density at 15°C	0.852	Flash point °C	206
Viscosity at 40°C / cSt	36	Pour point °C	-54
Viscosity at 100°C / cSt	7.4	Colour	Red
Viscosity index	178		

All technical data is provided for reference only.

7 - 2009