

## Product information



# SUNOCO

## Sunep range

**Description** SUNEP industrial gear oils are proven and accepted EP lubricants. They are exceptionally stable over a wide range of temperatures, have a high load-carrying capacity and separate quickly from water.

**Application** Recommended for use in spur, helical, bevel and worm gear configurations subject to heavy loads or shock loads. Lubrication of industrial gearboxes that require EP oils.

**Specifications** - DIN 51517 Part 3 CLP.  
- API GL-3

**Properties**

- Contains EP additives.
- Protection against corrosion, rust and wear.
- High load capacity.
- Viscosity stability.
- Water separation.

### Typical Analysis :

	68	100	150	220	320	460	680
Density at 15 °C	0.881	0.886	0.890	0.894	0.896	0.900	0.901
Viscosity at 40°C / cSt	68	100	150	220	320	460	680
Viscosity at 100°C / cSt	8.6	11.2	14.9	18.9	24.3	30.0	39.0
Viscosity index	97	97	97	97	97	97	97
Flash point °C	210	210	210	210	220	225	290
Pour point °C	-12	-12	-12	-12	-12	-12	-12
Timken load	65	65	65	65	65	65	65
FZG	12	12	12	12	12	12	12
Colour	3.0	L3.5	4.0	L4.5	L5.0	5.0	5.0

All technical data is provided for reference only.

8 - 2009