

Product information



SUNOCO

Sunfood Chain range

Description Fully synthetic food graded lubricant, particularly adapted for lubrication of chains and conveyors used next to or above foodstuff.

Application Particularly recommended for lubrication of conveyor chains, bearings, ball bearings, slides with hooks in food-processing industry, especially slaughterhouses, butcheries, meat industries, but also canning factories, bakeries, Viennese pastry factories, animal processing industries, food for cattle's, ready made meals, etc.
Can be used on drip, by spraying or with a brush by manual system or centralised greasing.

Specifications - NSF H1 Category registered.

Properties

- Formulation specially studied to avoid clogging and formation of deposit during the lubrication of conveyor chains.
- Very good stability at shearing: Food Chain keeps an oiliness of lubricating film under a large range of temperature of use.
- Its specific viscosities allow a lubrication of many kinds conveyor chains.

Typical analyses :

NSF Registration N°	139759	139760
ISO VG	150	320
Density at 15°C	0.839	0.845
Viscosity at 40°C / cSt	150	320
Viscosity at 100°C / cSt	19.2	34.1
Viscosity index	146	150
Flash point °C	280	280
Four ball test : Wearing / mm	0.35	0.35
Application range °C	-40 / +230	-40 / +250

All technical data is provided for reference only.

6 - 2009