



## SUNOCO Sunfood Comp range

**Description** Fully synthetic food graded compressor oil, with a high natural viscosity index.

**Application** All types of air compressors, as screw compressors, pallet compressors, piston compressors, where a synthetic lubricant is recommended. Also applicable in hydraulic circuits, jacks and vacuum pumps.

**Specifications**

- NSF H1 Category registered.
- meets : AFNOR E 60 200      CB HV
- DIN 51506                VD-L
- DIN 51354                FZG pass over 10

**Properties**

- Excellent shear resistance.
- Anti-oxidant, anti-wear and antirust properties.
- Neutral with joints.
- Colourless, odourless and insipid.
- Accidental contact with foodstuff will not damage the latter.

### Typical analyses :

NSF Registration N°	139761	139762	139763
ISO VG	46	68	100
Density at 15°C	0.830	0.832	0.835
Viscosity at 40°C / cSt	46	68	100
Viscosity at 100°C / cSt	8.5	11.7	14/15
Pour point °C	<-30	<-30	<-30
Four ball test : Wearing / mm	0.35	0.35	0.35
Demulsification with blade 40/37/3 / mm	<15	<15	<15

Oxidation PNEUROP DIN 51352			
Part 1 : - Conradson residue %	0.95	-	-
- Evaporation %	8.5	-	-
Part 2 : - Conradson residue %	1.7	-	-
- Evaporation %	17	-	-

All technical data is provided for reference only.

6 - 2009