

Product information



SUNOCO Sunvis 900 range

Description Hydraulic oil composed out of highly refined paraffinic base oils and enforced with additives to prevent oxidation, rust and foam.

Application Recommended for use in water- and steam turbines.
Prescribed for use in compressors and circulation systems and for lubrication of bearings. Recommended for a wide range of industrial applications not requiring special anti-wear properties.

Specifications - DIN 51524 Part 1 HL

Properties - Highly quality lubricating oil with anti-rust, -oxidation and -foam additives.
- Very low Conradson carbon content.
- Good water separation properties.

Typical analysis :

	915	922	932	946	968
density at 15°C	0.864	0.865	0.873	0.876	0.880
viscosity at 40°C / cSt	15	22	32	46	68
viscosity at 100°C / cSt	3.3	4.3	5.2	6.7	8.7
viscosity index	87	98	98	98	98
flash point °C	175	190	210	220	230
pour point °C	-24	-30	-24	-18	-15
TAN mg KOH/g	0.14	0.14	0.14	0.14	0.14
colour	L0.5	0.5	1.0	L1.5	L1.5

	9100	9150	9220	9320	9460
density at 15°C	0.883	0.886	0.890	0.894	0.898
viscosity at 40°C / cSt	100	150	220	320	460
viscosity at 100°C / cSt	12.3	14.8	18.9	24.2	30.7
viscosity index	98	98	96	96	96
flash point °C	246	260	271	276	301
pour point °C	-12	-9	-9	-9	-9
TAN mg KOH/g	0.14	0.14	0.14	0.14	0.14
colour	1.5	2.0	3.0	4.0	4.5

All technical data is provided for reference only.

10 - 2009